



Corporation

1-877-949-9477

KRYSTALITE™ INSTALLATION INSTRUCTIONS

EXISTING FILTER (for new filters skip to step 3).

STEP 1.

Remove dial valve of filter lid and empty existing water and media from filter tank. (A shop vac is useful for this task).

STEP 2.

Rinse out inside of tank and laterals with a garden hose (remove drain plug for this operation). At this point inspect the laterals and if defective replace or repair. Re-install drain plug and ½ fill filter tank with water.

STEP 3.

Slowly pour required amount of Krystalite™ into filter tank. Use approximately 50 lbs. of Krystalite™ to 100 lbs. of silica sand. (Note: most filters have the media quantity requirement printed on the label). Replace the dial valve or filter lid.

STEP 4.

Turn the dial valve to backwash, start pump and backwash for approximately 5 minutes or until backwashed water turns clear. Turn off pump, turn dial valve to rinse and run filter for 1 minute or until water turns clear.

STEP 5.

Turn pump off and move dial valve to filter position. Turn on the pump and note the pressure on the pressure gauge. This P.S.I. number is your filters optimum working pressure. An increase of pressure of 6-8 P.S.I. indicates your filter needs a backwash (step 4).

STEP 6.

Maintenance – Once a year, add 3 lbs. of table salt to pool skimmer while filter is in filter mode. Once salt is sucked clear, turn off filter and let sit overnight. Repeat step 4, then return to normal operation (step 5).

CANNON CORPORATION

1-877-949-9477